

Date: _____

Name: _____ Car # _____ Licence # _____

| # | Item | | | Requirements / Remarks |
|----|------------------------------------|--|--|--|
| 1 | Safety Harness | | | FIA/120T98 or SF116.1/FMWSS209. Expiry date: |
| 2 | Safety belt mounting points | | | Large washers top/bottom mounted to floor not seat |
| 3 | Tyres / Rims | | | 15 inch. Max 7J wide No magnesium or chrome |
| 4 | Gearbox | | | Wired drain plug and side cover no oil leaks |
| 5 | Gearbox Seal | | | Gearbox Seal Number: |
| 6 | Engine Seal | | | Engine Seal Number: |
| 7 | Chassis Seal | | | Chassis Seal Number: |
| 8 | Fuel tank | | | Protected by fire wall, breather away from exhaust |
| 9 | Fuel line | | | Outside of car otherwise braided hose |
| 10 | Brake hoses | | | Check cracks and fouling on wheels and suspension |
| 11 | Brake pedal travel | | | Firm pedal must not reach floor |
| 12 | Roll cage | | | Minimum 6 point / 38 mm / 1.6 mm tube wall |
| 13 | Fire extinguisher | | | 1,5kg rechargeable, serviced and certified every 12 months. Firstryker additional safety measure as per Circular 3of 2021 issued by MSA. Expiry date: |
| 14 | Battery | | | Battery Secured properly and terminals covered. |
| 15 | Cut out switch | | | Cut out switch Accessible from seat / remote cable / marked yellow on blue |
| 16 | Windscreen | | | Windscreen Laminated Glass. No cracks in drivers view |
| 17 | Side windows | | | Side windows Standard except certain cars Polycarbonate or Lexan 3mm thick |
| 18 | Safety net | | | Safety net Must be fitted to the roll cage NOT the drivers door |
| 19 | Wheel studs & nuts | | | Wheel studs & nuts Open ended must turn on 1.5 times diameter of thread |
| 20 | Bonnet catches | | | Bonnet catches Clip type added |
| 21 | Tow hooks - Straps | | | Tow hooks - Straps Easy access / Stickers marked TOW / Canvas nylon type straps |
| 22 | Competition number | | | Competition number Standard size black on white background |
| 23 | Suspension | | | Suspension All Tie rods, ball, and rose joints in good condition |
| 24 | Brake lights | | | Brake lights Must work when brake pedal pressed. Tape up if glass |
| 25 | Headlights and Indicators | | | Headlights and Indicators Must be fully functional tape up if glass |
| 26 | Sump drain plug / Filter | | | Sump drain plug / Filter Must be wired no oil leaks |
| 27 | Oil overflow tank | | | Oil overflow tank Check capacities (minimum 1 Liter) and mount away from exhaust |
| 28 | Mirrors | | | Rear view and 2 x side mirrors must be fitted |
| 29 | Silencers | | | Silencers Mounted correctly/good condition no excessive noise/maximum 96 decibels |
| 30 | Fire wall/Cockpit | | | Fire wall/Cockpit No holes to cockpit and/or floor |
| 31 | Race seat | | | Race seat Correctly mounted 4 x 8mm bolts minimum 8.8tensile |
| 32 | Body work | | | Body work No sharp edges or flapping body parts. Bumpers must be properly secured |
| 33 | Exhaust safety bracket | | | Exhaust safety bracket Across exhaust to stop falling to floor if mounting bracket breaks |
| 34 | Ballast weight | | | Ballast weight Secured properly / large washers or plates / lock nuts and 25 mm bolts |
| 35 | All components under bonnet secure | | | All components under bonnet secure No loose parts, catch tanks, and breathers etc |
| 36 | Steering column secured | | | Steering column secured Mounted firmly, no play |
| 37 | Sponsors/Stickers and decals | | | Sponsors/Stickers and decals all sponsor and safety stickers must be in accordance with the committee instructions |

Notes:

| |
|--|
| |
| |
| |

| | Driver Safety Equipment | | | |
|---------------------------------|---------------------------|--|--|--|
| 1 | Helmet/visor/HANS | | | |
| 2 | Underwear/socks/balaclava | | | |
| 3 | Race suit/gloves | | | |
| APPROVED FOR COMPETITION | | | | |
| | Signed by Scrutineer | | | |
| | Signed by VW Challenge TC | | | |